

KIXX ROCKDRILL

PNEUMATIC PERCUSSION TOOL LUBRICANT

DESCRIPTION

High performance lubricant for percussion-type air tools, which is formulated from highly refined mineral oils, EP and tackiness additives, emulsifiers, rust and corrosion inhibitors, and antifoam and anti-fogging agents.

APPLICATIONS

- Percussion-type air tools operating under wet or dry conditions, including: Rock drills.
- Concrete and pavement breakers (jackhammers).
- Tampers.
- Rammers.
- Riveting and chipping hammers, etc.
- Centralized lubricators of larger crawler-mounted drill rigs.

PERFORMANCE

- ISO 6743/11

BENEFITS

- Maximum working life of equipment: Special EP and high film strength oiliness additives withstand shock loads under boundary lubrication conditions and protect components against wear.
- Protects surfaces in wet conditions: Superior emulsification properties prevent water wash-off from critical areas when operating with wet air, or during hollow rod “wet drilling” operations.
- Effective rust and corrosion inhibitor system protects critical components in wet air or “wet drilling” operation.

KEY PROPERTIES

Product Name	KIXX ROCKDRILL
ISO VG grade	100
Kinematic Viscosity @ 40°C (mm ² /s)	96
Kinematic Viscosity @100°C (mm ² /s)	10.9
Viscosity Index	107
Copper Corrosion, 3hr @100°C	1a
Pour Point	-27