

KIXX 10W PLUS

DIESEL ENGINE OIL

API CF/CD, SAE 10W

DESCRIPTION

KIXX 10W Plus high quality, mono-grade, heavy-duty diesel engine oil specially designed to lubricate diesel engines requiring API CD performance lubricants. The level of alkaline reserve makes it particularly suitable for use with high sulfur fuels at appropriate oil drain intervals.

APPLICATIONS

- Diesel Engines (High speed, Four Stroke, Turbocharged or Naturally Aspirated)
- Commercial road transport
- Off-highway
- High speed diesel engines in marine service (e.g., fishing, river transport, etc.)
- Manual transmissions (where oil type and viscosity are appropriate)
- Mobile hydraulic systems (where oil type and viscosity are appropriate)

PERFORMANCE STANDARDS

- API CF/CD
- E-DL 2 of IS 13656-2002
- MIL-L-21404D

BENEFITS

- Saves on Maintenance
- Prolongs period between overhauls
- Preserves power and performance
- Longer oil drain intervals

KEY PROPERTIES

SAE GRADES	10W
Viscosity @ 40°C (mm ² /s)	38.14
Viscosity @100°C (mm ² /s)	6.2
Viscosity Index	109
Pour Point (°C)	-30
Flash Point (°C)	226
TBN, mg KOH/g, (ASTM 2896)	9.1

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by GS Caltex Corporation