

GS Caltex India Private Limited

Way Lubricant 68

Slideway Oil

Global Premium Lubricants

Way Lubricant 68

Slideway Oil

ISO 68

GS Waylube 68 is of a premium quality based on highly refined, high viscosity index mineral oil to provide effective lubrication of machine slide-ways.

It contains tackiness and especially selective additives assuring efficient lubrication and resist stick-slip.

GS Waylube 68 has a unique combination of exceptional frictional characteristics with high extreme pressure performance capability.

APPLICATIONS

- All machine tool parts, including bearings and gearboxes
- Machine tools slideways

PERFORMANCE STANDARDS

- General Motors LS-2 Way Oil Performance Level (LW-06-1-04)
- Cincinnati Machine Performance Level (P-47)
 Central Luonicants

BENEFITS

- Ash-less, light color technology
- Exceptional frictional characteristics as measured by stick-slip
- Strong demulsifying ability and water separation profile
- Capable of high extreme pressure performance

KEY PROPERTIES

ſ	ISO Grade	Appearance	Viscosity (mm²/s)		Viscosity	Pour	Flash	Rust Test D665
			@40°C	@100°C	Index	Point (°C)	Point (°C)	(A&B), 24hrs
	68	Clear, Bright	69.19	9.30	112	-27	234	Pass

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected.

It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by GS Caltex Corporation.

(10/2012)



GS Caltex India Private Limited |