

KIXX HYDRO SUPER

HYDRAULIC FLUID

DESCRIPTION

KIXX Hydro Super is a mid range anti-wear hydraulic fluid designed for use in mobile and stationary hydraulic systems.

APPLICATIONS

- All Industrial hydraulic systems, Mobile and construction equipment hydraulic system, Plastic injection molding machines.

PERFORMANCE

- Denison Hydraulics HF-0 (ISO 32, 46, 68)
- Vickers M-2952-S, I-286-S [industrial applications] M-2950-S [mobile applications]
- Cincinnati Milacron P-68 (ISO 32), P-69 (ISO 68), P-70 (ISO 46)
- ISO Standard 6743 Part 4, Type HM
- DIN 51524 Part 2, HLP (ISO 32, 46, 68)

BENEFITS

- Advanced anti-wear additive package incorporated reduces wear by protecting surfaces.
- Operating reliability, effective rust and oxidation inhibitor prevents from rust formation and deposits, varnish and sludge.

KEY PROPERTIES

ISO GRADE	32	46	68
Kinematic Viscosity @ 40°C (mm ² /s)	31.8	46.3	67.5
Viscosity Index	96	97	97
Pour Point (°C)	-18	-15	-15
Flash Point (°C, COC)	212	220	236
Rust Test (D665)	PASS	PASS	PASS