

KIXX HYDRO AF

Zinc Free Anti-Wear Hydraulic Fluid

DESCRIPTION

GS Hydro AF hydraulic oils are formulated with high quality base oils and an ash-less additive system that provides superior oxidation stability, water separability, foam suppression and protection against wear, rust and corrosion. They are designed to give maximum protection to hydraulic pumps in high temperature industrial applications as well as in environmentally sensitive areas

Benefits

- Premium performance
- Superior oxidation stability
- Excellent anti-wear properties

Performance Standard

- Denison Hydraulics HF-0, HF-1, HF-2
- ISO 11158 – HM
- DIN 51524 Part II
- Eaton Vickers I-286 S (Industrial equipment)
- Eaton-Vickers M-2950-S (Mobile equipment)

- **KEY PROPERTIES**

ISO VG	46	68
Density, kg/liter @15°C	0.850	0.859
Viscosity (mm ² /s) @40°C	45.8	68.8
Viscosity (mm ² /s) @100°C	7.4	9.5
Viscosity Index	124	116
Pour Point (°C)	-39	-36
Flash Point (°C)	236	254

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by GS Caltex Corporation