

# KIXX COMPRESSOR OIL 68

## MINERAL COMPRESSOR OIL

### DESCRIPTION

KIXX Compressor oil 68 is premium oil specially developed for oil flooded screw and sliding vane type compressor to provide satisfactory lubrication under wide range of operating temperatures and load conditions.

KIXX Compressor oil 68 is formulated using advanced ash-less technology which reduces sludge deposits.

### APPLICATIONS

KIXX Compressor oil 68 is recommended for use in oil flooded screw compressors of various OEMs. The product is also suitable for use in sliding vane.

### PERFORMANCE STANDARDS

- ISO 6743 - DAH
- DIN 51506 VDL

### BENEFITS

- Excellent oxidation and thermal stability.
- Improved ash-less technology.
- Improved water separability.
- Low wear to improve anti-wear and lubricating properties.
- Excellent performance at high temperature and good start ability in cold temperature.

### KEY PROPERTIES

SAE Grade	68
Kinematic Viscosity @ 40°C (mm <sup>2</sup> /s)	67.76
Kinematic Viscosity @100°C (mm <sup>2</sup> /s)	9.10
Viscosity Index	110
TAN	0.57
Flash Point (°C, COC)	238
Demulsibility @ 54°C 40-40-0 (10)	40-40-0 (10)
Rust Test D665 (A&B), 24hrs	Pass